

GLASS SLIM



MODERN LOW PROFILE WALL SYSTEM WITH HIGH ADJUSTABILITY AND SIMPLIFIED INSTALLATION



PRODUCT FEATURES



Enhanced light penetration
Minimal extrusions
Surface or recessed mounted
10mm-25mm, 0.39"-0.98" installation tolerance

Single glazing
Integrated floor to ceiling pivot doors available as frameless, acoustic framed, or solid wood

STANDARDS

Wall thickness:	39mm (1 1/2")
Minimum panel width:	200mm (8")
Maximum panel width:	1200mm (4')
Maximum panel height:	3000mm (10')
Top profile height:	50mm (2")
Bottom profile height:	50mm (2")
Sound Rating:	36 with 10mm Acoustic Laminated Glass 39 with 16mm Acoustic Laminated Glass

GLASS THICKNESS

10, 12, or 16mm (3/8", 1/2", or 5/8")

STANDARD JOINT

High transparency acoustic I shaped PVC profile

STANDARD WARRANTY

5 years

DOORS



Opaque Door:	50mm (2")
Glass Door:	10mm (3/8")
Framed Single Glazed Door:	50mm (2")
WOD Glass Slim:	50mm (2")
50mm Double Glazed Door:	50mm (2")